



**FACILITY SYSTEMS**  
TECNOLOGIA PARA RETAIL

**SOPORTE TÉCNICO**

**TIEMPO DE  
INACTIVIDAD CERO**

**SOLUCIONES LLAVE  
EN MANO**

## FS-RELE-GPS



**FS-RELE-GPS** el localizador GPS para vehículos FS-RELE-GPS brinda múltiples alarmas inteligentes, como Desconectado, Corte de energía, Batería baja, Geo-cerca, Alerta de velocidad. Con un chip de acelerómetro y GPS de alta precisión para detectar conductas inseguras.

Localización GPS: GPS + LBS, precisión de ubicación GPS <10m, tiempo de actualización de ubicación GPS rápido a 10s, ubicación y seguimiento en tiempo real, históricos en la plataforma.

**Control remoto que corta / reanuda el suministro de aceite al automóvil**



GPS+LBS+WIFI+BD+GLONASS LOCATION

Supports GPS&LBS+WIFI&BD&GLONASS.the users are able to use it outside and indoor globally.



VIBRATION ALERT

Build-in sensitive vibration sensor even if a slight vibration for 3second the device will send alarm to owner.



GEO-FENCE

Geo-fence will help you make safe area for your car/families .if carrier is out of safe area the device will send alarm to owner.



HISTORICAL ROUTES

The server can store the data for half year so you can check the historical routes in APP&Web platform at any time.



MOVE ALERT

As long as the car is driven far from the sidtace which was set the device will send alarm to the owner via SMS&APP.



OVER SPEED ALERT

Build-in 3G-sensor ,Once the driver is beyond the safe speed that device will send alarm to the user.



CUT OFF/RESUME CAR ENGINE

Remoting control cutting off/resume oil supply to car.



**FACILITY SYSTEMS**  
TECNOLOGIA PARA RETAIL

## FS-RELE-GPS

SOPORTE TÉCNICO

TIEMPO DE  
INACTIVIDAD CERO

SOLUCIONES LLAVE  
EN MANO

Content	Specs.
Dim.	31mm x 31mm x 57mm
Weight	50g
Network	GSM/GPRS
Band	850/900/1800/1900Mhz
GPS chip	UBLOX
GPS sensitivity	-159dBm
GPS accuracy	5m
Time To First Fix	Cold status 35-80 s Warm status 35s Hot status 1s
Operating Voltage	10—50V
Battery	Rechargeable 3.7V 100mAh Li-ion battery
Standby	1 days
Storage Temp.	-40°C to +85°C
Operation Temp.	-20°C to +55°C
Humidity	5%--95% non-condensing